



www.vacutec.com

1591 Sunland Lane, Costa Mesa, CA 92626 | U.S.A.
Tel: 888.822.8832 | Fax: 714.433.2840 | Email: Info@vacutec.com

MATERIAL SAFETY DATA SHEET

10-16-03

This MSDS follows The American National Standards Institute (ANSI) suggested format (Z400.1-1993)

Section 1: Chemical Product and Company Identification

PRODUCT NAME

Diagnostic Smoke Solution

GENERIC CHEMICAL NAME / USDA AUTH.

Pharmaceutical USP Petroleum Blend / H1

PART NUMBER

P3416

FOR PRODUCT

Vacutec PRO2000 (model 2000)

COMPANY

Worldwide Vapor, Inc.

ADDRESS

1591 Sunland Lane, Costa Mesa, CA 92626 / U.S.A.

EMERGENCY TELEPHONE NUMBER

1-800-255-3924 Chem-Tel (24 hours)

TELEPHONE NUMBER FOR INFORMATION

714-438-1388

Section 2: Composition, Information or Ingredients

PRODUCT HAZARD RATING*: HEALTH RISK = 0, FLAMMABILITY = 1, REACTIVITY = 0

[*Hazard Rating System Equivalence: 0 = Very Least, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme]

COMPONENTS — OSHA PELs

ACGIH TLVs

OIL MIST IN AIR — 5mg/m3

5mg/m3

NOT A CONTROLLED PRODUCT UNDER (WHMIS) - Canada

Section 3: Hazard Identification

THRESHOLD LIMIT VALUE: 5mg/m3 for oil mist in air. OSHA Regulation 29 CFR 1910.1000

EFFECTS OF EXTREME OVEREXPOSURE: This is basically a Safe product. However, human health risks vary from person to person. As with any petroleum base product, reasonable caution should be taken to avoid prolonged and repeated exposure to the base product. Overexposure to skin and eyes may cause irritation.

THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY. If base product is swallowed it presents a low risk of aspiration into the lungs. In the event that swallowing the base product in small quantities does take place, it is expected to pass through the system without symptoms. As with any petroleum base product: If large quantities are swallowed and subsequently aspirated into the lungs, mild to severe pulmonary injury may occur.

CARCINOGENS: NTP? NONE

IARC MONOGRAPHS? NONE

OSHA REGULATED? NO

Section 4: First Aid Measures and Precautions

The following precautions are common sense First Aid Measures for our Product or any petroleum based product:

EYE CONTACT: Flush eyes with clean water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.

SKIN CONTACT: Remove any contaminated clothing and wash affected skin area with soap and warm water.

INHALATION: Inhalation at ambient temperatures is not commonly a problem. If overcome by excessive exposure to vapors, you should remove from exposure to well ventilated area. Some people may experience dizziness, drowsiness or nausea. If symptoms persist, consult a physician. It is always a good measure of precaution to avoid excessive inhalation of byproduct.

INGESTION: If ingested, the precaution is to call a physician or our emergency number immediately. Do not induce vomiting.

Section 5: Fire-Fighting Measures

FLASH POINT (Method Used): 335-510°F or 168-265°C (COC) **LEL:** 0.9% **UEL:** 7.0%

EXTINGUISHING MEDIA: Water Spray (Fog), Foam, Dry Chemical and Carbon Dioxide.

SPECIAL FIRE FIGHTING PROCEDURES: Cool exposed container with water. Use air-supplied breathing equipment for enclosed or confined spaces.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Do not store or mix base chemical with strong oxidants. Do not cut, drill, grind, or weld container, as this may cause explosion.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS ACCIDENTALLY SPILLED:

Recover liquid, wash remainder with suitable petroleum solvent or add absorbent. As with all petroleum products, keep out of sewers and water courses. Advise authorities if ever any petroleum product has entered or may enter sewers or water courses.

WASTE DISPOSAL METHOD:

Assure conformity with applicable local disposal regulations.

Section 7: Handling and Storage

Do not handle or store near heat, flames or strong oxidants.

Section 8: Exposure Controls and Personal Protection

Use this product in a well ventilated area.

Section 9: Physical and Chemical Properties

BOILING POINT: >550°F (>288°C)

VAPOR PRESSURE (MM HG.): <1.0 @ 68°F

VAPOR DENSITY (AIR = 1): >5

SOLUBILITY IN WATER: Negligible

SPECIFIC GRAVITY (H₂O=1): 0.87-0.89

MELTING POINT: Liquid

EVAPORATIVE RATE (BUTYL ACETATE = 1): <0.01

APPEARANCE AND ODOR: Colorless to Very Pale Amber.
Mineral Oil Type Odor.

Section 10: Stability and Reactivity

STABILITY: Very Stable

CONDITIONS TO AVOID: Not Applicable

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidants such as liquid chlorine and concentrated oxygen.

HAZARDOUS POLYMERIZATION: Will not occur.

Section 11: Toxicological Information

HAZARD IDENTIFICATION OF CARCINOGENICITY, REPRODUCTIVE EFFECTS, TARGET ORGAN EFFECTS: This product does not have Carcinogens — Section 11 does not apply to this product.

Section 12: Ecological Information

Section 12 does not apply to this product.

Section 13: Disposal Considerations

All components of this Product are made from new materials. Some components of this Product are manufactured from Reclaimable Materials: We recommend this product be returned to manufacturer for its reclaimable properties. Otherwise State and/or City Regulations should be observed for proper disposal of this product.

Section 14: Transport Information

Refer To Section 3 For Any Related or Pertinent Information That May Apply.

Section 15: Regulatory Information

Section 15 does not apply to this product.

Section 16: Other Information

For Any Questions Regarding This Material Safety Data Sheet: Contact Worldwide Vapor, Inc. 714-438.1388

The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Worldwide Vapor, Inc. The data on these sheets relates only to the specific material designated herein. Worldwide Vapor, Inc. assumes no legal responsibility for use or reliance upon this data.